



New Enterprise Stone & Lime Co., Inc.

3580 Division Hwy. • East Earl, PA 17519 • Lancaster Area Office: 717-354-1300

-Product Specifications-

ORIGINAL DIAMOND-TEX®

ASTM D422*

Particle-Size Analysis of Soils

SIEVE SIZE	PERCENT PASSING
# 4	100.0%
# 8	89.7%
# 10	86.7%
# 16	77.3%
# 30	62.2%
# 50	51.1%
# 100	42.3%
# 200	35.0%

Sieve Analysis Soil Classification

<u>SOIL TYPE</u>	<u>CONTENT</u>
Sand:	65%
Silt:	24%
Clay:	11%

ASTM D698

Standard Proctor Analysis

Optimum Moisture Content: 7.8%

Maximum Dry Density (Loose)

LB/Cu. Ft. 133.40

TN/Cu. Yd. 1.80

Maximum Wet Density (Compacted)

LB/Cu. Ft. 143.80

TN/Cu. Yd. 1.94

*Test results are an average of tests performed by the Diamond-Tex® quality control laboratory and an independent lab. Actual test results for a specific sample may vary slightly without affecting product performance.

Korey Swope
Quality Control Technician
Revised 2/15/2016

For additional product information contact:
Anthony Paolino
New Enterprise Stone & Lime Co., Inc.
717-617-8247
apaolino@nesl.com www.nesl.com